

FIRESURE FM AND LPC TYPE FLOWMETERS**RM5,080.00 – RM6,640.00****Firesure Duo - Flange Flowmeter**

LPCB & FM Approvals for Sprinkler Fire Pump Testing

SINGLE combined dm^3 / min and US GPM tube

- Suitable for LPC and FM installations.
- Stable easy to read flow indication.

ISOLATION VALVES at inlet & outlet to indicator

- Provides a permanent, safe and secure installation.
- Allows isolation from main pipe eliminating shocks at pump start up.
- Air is automatically vented when valves are opened.

Horizontal, inclined & vertical WAFER FLANGE connection

- Flexibility in design & site positioning.

- Compact and simple installation.

SKU: N/A | **Categories:** [Fire Sprinkler System](#) | **Tags:** [Fire Sprinkler System](#)



VARIATIONS

Image	SKU	Price	Stock Status	Stock Quantity	Description	Part No.
		RM5,080.00				DUO F450
		RM6,640.00				DUO F1000

PRODUCT DESCRIPTION

TECHNICAL DATA

Pipe OD	Nominal	Meter Code	Flow Test Ranges	Pump Duty	LPC Approval	FM Approval
mm	mm Inches		LPCB dm ³ / min	US GPM	Ref.	Ref. FS
			FM US GPM			

60.3	50	2	LF100*	150 -700		100	464a/01	
88.9	80	3	DUO F200	300 - 1600	100 - 400	150; 200	464a/02	80FLFM
114.3	100	4	DUO F450	500 - 3500	150 - 900	250; 300; 450	464a/03	100FLFM
165.1 / 168.3	150	6	DUO F1000	900 - 7900	250 - 2000	500; 750; 1000	464a/04	150FLFM
219.1	200	8	DUO F2000	2000 - 15000	750 - 4000	1250; 1500; 2000	464a/05	200FLFM



ADDITIONAL INFORMATION

Part No. DUO F450, DUO F1000

